Tetra © Pond

Filtration Fountain Kits

Complete Filtration for Small and Mid-Size Ponds



12 ft. cord 120 VAC 60 Hz

Fountain Assembly

- Includes 3 fountain heads
- Swivel adjuster levels fountain heads
- Diverter assembly
 - Fits 1 in., ¾ in., ½ in. ID tubing (fittings included)
 - Adjustment valve for regulating flow to fountain head and/or auxillary water feature

Pre-Filter

- Keeps small ponds clean
- Reduces pump and fountain clogging
- · Foam insert included
- Threads directly into pump inlet

Submersible Pump

- 325 gallons per hour at 1 foot (maximum pumping height 7.2 ft.)
- Reliable magnetic drive technology
- Energy-efficient



Ideal for small pre-formed ponds







Fountain heads create 3 different patterns (included with FK3 & FK5 kits)

FK5 Filtration Fountain Kit



Fountain Assembly

- Includes 3 fountain heads
- Swivel adjuster levels fountain heads
- Diverter assembly
 - Fits 1 in., ¾ in., ½ in. ID tubing (fittings included)
 - Adjustment valve for regulating flow to fountain head and/or auxillary water feature

Submersible Filter

- Keeps pond clean
- Reduces pump and fountain clogging
- Coarse and fine pad included
- Tubing and fittings for pump connection included

Submersible Pump

- 325 gallons per hour at 1 foot (maximum pumping height 7.2 ft)
- Reliable magnetic drive technology
- Energy-efficient



12 ft. cord

120 VAC

60 Hz



Submersible Flat Box Filter

- Keeps ponds clean and prevents pump and fountain heads from clogging.
- Fits a wide variety of pumps 200 to 2000 gph.

• For ponds up to 500 gallons.







SF1 includes:

- Filter box with filter-to-hose fitting
- Coarse and fine foam pads
- Tubing 12 in. x 1 in. ID
- 3 fittings for attaching hose to various pump inlets:
 - ¾ in. male thread with 1 in. ID hose barb
 - 1 in. male thread with 1 in. ID hose
 - 1¼ in. male thread with 1 in. ID hose barb

Fits all TetraPond DynaMag Pumps (pump not included)

- DynaMag 250 (250 gallons per hour)
- DynaMag 500 (500 gallons per hour)
- DynaMag 750 (750 gallons per hour)





Item	Model	For Ponds	Pump	Description	Pump Input Fittings	Pump Discharge Fittings
#26594	FK3	under 100 gallons	325 gph pump	Cylinder Pre-Filter	¾ in. male thread	Fits 1 in., ¾ in., ½ in. ID tubing
#26593	FK5	50 to 250 gallons	325 gph pump	Flat Box Filter with coarse and fine foam pads	¾ in. male thread	Fits 1 in., ¾ in., ½ in. ID tubing
#26592	SF1	up to 500 gallons	Use with pump between 200 to 2000 gph	Flat Box Filter with coarse and fine foam pads	¾ in. male thread 1 in. male thread 1¼ in. male thread	N/A